



TROPICANA GOLD MINE

ANALYST VISIT – 3RD MARCH 2014

DUNCAN GIBBS – GENERAL MANAGER



Independence Group



ANGLO**GOLD**ASHANTI

ANGLOGOLD ASHANTI LTD DISCLAIMER

Certain statements contained in this document, other than statements of historical fact, including, without limitation, those concerning the economic outlook for the gold mining industry, expectations regarding gold prices, production, cash costs, cost savings and other operating results, return on equity, productivity improvements, growth prospects and outlook of AngloGold Ashanti's operations, individually or in the aggregate, including the achievement of project milestones, commencement and completion of commercial operations of certain of AngloGold Ashanti's exploration and production projects and the completion of acquisitions and dispositions, AngloGold Ashanti's liquidity and capital resources and capital expenditures and the outcome and consequence of any potential or pending litigation or regulatory proceedings or environmental issues, are forward-looking statements regarding AngloGold Ashanti's operations, economic performance and financial condition. These forward-looking statements or forecasts involve known and unknown risks, uncertainties and other factors that may cause AngloGold Ashanti's actual results, performance or achievements to differ materially from the anticipated results, performance or achievements expressed or implied in these forward-looking statements. Although AngloGold Ashanti believes that the expectations reflected in such forward-looking statements and forecasts are reasonable, no assurance can be given that such expectations will prove to have been correct. Accordingly, results could differ materially from those set out in the forward-looking statements as a result of, among other factors, changes in economic, social and political and market conditions, the success of business and operating initiatives, changes in the regulatory environment and other government actions, including environmental approvals, fluctuations in gold prices and exchange rates, the outcome of pending or future litigation proceedings, and business and operational risk management. For a discussion of such risk factors, refer to the prospectus supplement to AngloGold Ashanti's prospectus dated 17 July 2012 that was filed with the United States Securities and Exchange Commission ("SEC") on 26 July 2013. These factors are not necessarily all of the important factors that could cause AngloGold Ashanti's actual results to differ materially from those expressed in any forward-looking statements. Other unknown or unpredictable factors could also have material adverse effects on future results. Consequently, readers are cautioned not to place undue reliance on forward-looking statements. AngloGold Ashanti undertakes no obligation to update publicly or release any revisions to these forward-looking statements to reflect events or circumstances after the date hereof or to reflect the occurrence of unanticipated events, except to the extent required by applicable law. All subsequent written or oral forward-looking statements attributable to AngloGold Ashanti or any person acting on its behalf are qualified by the cautionary statements herein.

This communication may contain certain "Non-GAAP" financial measures. AngloGold Ashanti utilises certain Non-GAAP performance measures and ratios in managing its business. Non-GAAP financial measures should be viewed in addition to, and not as an alternative for, the reported operating results or cash flow from operations or any other measures of performance prepared in accordance with IFRS. In addition, the presentation of these measures may not be comparable to similarly titled measures other companies may use. AngloGold Ashanti posts information that is important to investors on the main page of its website at www.anglogoldashanti.com and under the "Investors" tab on the main page. This information is updated regularly. Investors should visit this website to obtain important information about AngloGold Ashanti.

INDEPENDENCE GROUP NL DISCLAIMER

Certain oral and written statements contained or incorporated by reference in this presentation, including information as to the future financial or operating performance of the Company and its projects, constitute forward-looking statements. All statements, other than statements of historical fact, are forward-looking statements. The words “believe”, “expect”, “anticipate”, “contemplate”, “target”, “plan”, “intend”, “continue”, “budget”, “estimate”, “may”, “will”, “schedule” and similar expressions identify forward-looking statements.

Forward-looking statements include, among other things, statements regarding targets, estimates and assumptions in respect of nickel, gold or other metal production and prices, operating costs and results, capital expenditures, mineral reserves and mineral resources and anticipated grades and recovery rates. Forward-looking statements are necessarily based upon a number of estimates and assumptions related to future business, economic, market, political, social and other conditions that, while considered reasonable by the Company, are inherently subject to significant uncertainties and contingencies. Many known and unknown factors could cause actual events or results to differ materially from estimated or anticipated events or results reflected in such forward-looking statements. Such factors include, but are not limited to: competition; mineral prices; ability to meet additional funding requirements; exploration, development and operating risks; uninsurable risks; uncertainties inherent in ore reserve and resource estimates; dependence on third party smelting facilities; environmental regulation and liability; currency risks; effects of inflation on results of operations; factors relating to title to properties; native title and aboriginal heritage issues; dependence on key personnel; and share price volatility and also include unanticipated and unusual events, many of which are beyond the Company’s ability to control or predict.

The Company disclaims any intent or obligation to update any forward-looking statements, whether as a result of new information, future events or results or otherwise. All forward-looking statements made in this presentation are qualified by the foregoing cautionary statements. Investors are cautioned that forward-looking statements are not guarantees of future performance and, accordingly, not to put undue reliance on such statements.

Independence Group NL

ABN 46 092 786 304

KEY FACTS 100% PROJECT

Location: 330 km ENE of Kalgoorlie in Western Australia

Ownership: AngloGold Ashanti Australia Ltd (70% and manager), Independence Group NL (30%)

Discovered: August 2005

Approved: November 2010


Production start: September 2013

Forecast production 2014: 485,000 – 528,000 oz

Production December 2013 quarter: 95,050 oz


Ore Reserve* (as at December 31, 2013): 3.76Moz



Mineral Resources* (as at December 31, 2013): 7.72Moz






* Details of Ore Reserve and Mineral Resources, and JORC Statements are the end of this presentation.

SITE LAYOUT





HAVANA GRADE CONTROL SECTION



MINING CONTRACT

Scope of Contract with Macmahon

- ▶ Load and haul
- ▶ Drill and blast
- ▶ Grade control (Wallis Drilling)
- ▶ Crusher feed
- ▶ Carey Mining (indigenous labour/equipment)
- ▶ Short term planning
- ▶ MineStar FMS operation
- ▶ Bulk and selective mining
- ▶ Bulk TSF lifts

Form of Contract


- ▶ Alliance structure – working together to maximise productivity and resolve issues
- ▶ Schedule of rates with annual re-price based on open-book cost model



MINING FLEET


- ▶ 1x CAT 6040 Excavator – 24 m³, 525 t
- ▶ 2x CAT 6050 Excavators – 20 m³, 400 t
- ▶ 15x CAT 793F Off Highway Trucks – 226 t capacity / 390 t gross
- ▶ 2x CAT MD6240 – 229 mm holes, 62 t
- ▶ 2x Sandvik DR560/580 – Down hole hammer, 33 t
- ▶ 1x Sandvik DR580 GC – 50 m long holes, 33 t
- ▶ 1x Hitachi EX2500 Excavator, rehandle
- ▶ 3x Cat 785B Off Highway Trucks, rehandle
- ▶ 4x CAT D10T track dozers
- ▶ 3x CAT 777D Water carts, 85 kL
- ▶ 1x Cat 336D Excavator
- ▶ 2x CAT 992 Front End Loaders
- ▶ 1x Cat 966 Front End Loader
- ▶ 1x 24M CAT Grader, 1x 16H CAT Grader
- ▶ 1x 854K CAT Wheel dozer
- ▶ 1x CS583E Roller
- ▶ 1x Hitachi EX1200 Excavator

LIFE OF MINE SCHEDULE



MINESTAR FLEET

- ▶ Automatic optimised dispatch of trucks to excavators
- ▶ Removes people and equipment from mining areas
- ▶ Ability to gather and use information to optimise the way we work




MINESTAR TERRAIN FOR DRILLING

- ▶ Drill hole accuracy to ~100 mm
- ▶ Greatly reduced requirement for surveyors
- ▶ Easier and safer for operators





GEOTECHNICAL ANALYSIS

Utilising iSite allows faster and improved evaluation





MONTHLY GLOBAL RESOURCE TO GC CONVERSION

Production Reconciliation Chain




MONTHLY GLOBAL PLANNED DILUTION

Production Reconciliation Chain





RECONCILIATIONS BY FLITCH

Production Reconciliation Chain




> 0.6 – 1.2 g/t cut





RECONCILIATIONS BY FLITCH



Production Reconciliation Chain



> 1.2 g/t cut off (Mill Feed)





MONTHLY UNPLANNED DILUTION





RECONCILIATIONS TO THE MILL (CV01 TO MINE CRUSHED)

Production Reconciliation Chain




MINE CALL FACTOR

Production Reconciliation Chain




INTEGRATED PLANNING MODEL



....forms a link between Evaluation, Short to Medium Term Scheduling, Production and Processing

GEO MET PROGRESS




Geometallurgical Parameter – Identification of parameters that can be used in geological modelling, which can add value in the milling and mining processes.


Proxy - Data that has been identified that can be used to correlate the behaviour of the Geometallurgical parameter or predict the behaviour of the parameter.

Technique - Quantative or Qualitative measure used to calculate the proxy


PLANT FLOWSHEET




TONNES MILLED



GRIND SIZE



RECOVERY



PROCESSING MINE REPORTING SYSTEM

MISWeb Plant Management

PMRS Tropicana Home Diagrams Data Entry Reports Alarms & Events

Tropicana Data Entry Plant Overview

Plant Overview

« Previous 19/11/2013 Night Shift Next »

Primary Crusher

Options	Measurement	Units	Actual
OK	CV01 weightometer tonnes	Total t	2,569
OK	CV01 - Moisture %	Time Avg. %	
OK	Primary Crushing - 80% passing size fraction	Time Avg. mm	
OK	Primary Crusher Operating Hours	Total hrs	4.0

Popup Quick View

HPGR

Options	Measurement	Units	Actual	Adjust
OK	CV05 moisture %	Time Avg. %	4.5%	Adjust
OK	CV06 weightometer tonnes	Total t	7,556	Adjust
OK	CV06 80% passing size fraction	Time Avg. mm		Adjust
OK	HPGR operating time	Total hrs	6.0	Adjust

Save Page

Popup Quick View

Assay Results
Load assay results from sample batch (SIF) files and review assay result data that has already been imported into PMRS.

Delay Accounting
Accounting system for delayed equipment.

Plant Overview
Entry of basic production data for each shift.

Shift Handover
Shift leader handover notes entry

Consumables & Reagents
Entry and/or review of consumables and reagent data for each production date.

Stockpile Management
Entry of stockpile related data for each shift.

Gold Stripping Process
Manual entry of measurements for each 'strip'

Bullion Entry
Enter all Bullion related values for this Operation.

GIC Survey Entry
Enter all GIC survey related values for a given survey date.

Leaching & Adsorption

Options	Measurement
OK	Leach Feed Tonnage
OK	Leach Feed Solids - AU grade
OK	Leach Feed Solution - AU grade
OK	Leach Feed - % solids
OK	Final Tails Tonnage
OK	Final Tails Solids - Au grade
OK	Final Tails Solution - Au grade
OK	Final Tails - % Solids

Reports Alarms & Events

- PMRS001 - Daily KPI report**
Processing department daily KPI report
- TGMP002 - Tropicana Weekly KPI Report**
Processing department weekly KPI report.
- TGMP001 - Tropicana Monthly KPI Report**
Processing department monthly KPI report.
- PMRS005 - Reagent Levels**
Displays the latest reagent levels at the end of the last shift for the Tropicana Gold Mine.
- PMRS010 - Delay Log Summary**
This report shows total delay time by productive unit, time class etc. In addition, you can select a summary grouping which is used to create a chart and high level summary table at the end of the ..
- PMRS011 - Delay Log Detail**
Full detail view of delay log. All delay log entries matching selected filters are shown.
- TGMP003 - Tropicana Bullion Summary Report**
Bullion summary report to show details of all bullion poured and shipped within

1. Permit to Work Request

Number	Primary Plant Item	Start Date/Time	Expiry Date/Time	Short Description	Location	Work Group	RIC	State
AGAA-PR-27	-	25-May-2013 06:00	25-May-2013 18:00	Clean out dump valve		Operations	Jason Crane	Planning
AGAA-PR-25	PPP-MIL-BLML-ML001-HE004 - HEATER, MOTOR 02	25-May-2013 06:00	25-May-2013 18:00	test hira		Maintenance Mechanical	Paul Chalmers	Submitted
AGAA-PR-19	-	25-May-2013 06:00	25-May-2013 18:00				Curtis Atlick	Planning
AGAA-PR-16	-	25-May-2013 06:00	25-May-2013 18:00				Paul Chalmers	Planning
AGAA-PR-5	-	25-May-2013 06:00	24-May-2013 18:00	123			sage sage	Planning
AGAA-PR-14	-	24-May-2013 06:00	24-May-2013 18:00				Tropicana SysAdmin	Planning
AGAA-PR-13	-	24-May-2013 06:00	24-May-2013 18:00				Tropicana SysAdmin	Planning
AGAA-PR-12	-	24-May-2013 06:00	24-May-2013 18:00				Tropicana SysAdmin	Planning
AGAA-PR-11	-	24-May-2013 06:00	24-May-2013 18:00				Tropicana SysAdmin	Planning
AGAA-PR-9	-	24-May-2013 06:00	24-May-2013 18:00				sage sage	Planning
AGAA-PR-8	-	24-May-2013 06:00	24-May-2013 18:00				Paul Chalmers	Planning
AGAA-PR-7	-	24-May-2013 06:00	24-May-2013 18:00				Paul Chalmers	Planning
AGAA-PR-6	-	24-May-2013 06:00	24-May-2013 18:00				sage sage	Planning
AGAA-PR-4	-	24-May-2013 06:00	24-May-2013 18:00				Paul Chalmers	Planning
AGAA-PR-3	-	24-May-2013 06:00	24-May-2013 18:00				sage sage	Planning
AGAA-PR-2	-	24-May-2013 06:00	24-May-2013 18:00				sage sage	Planning
AGAA-PR-1	-	24-May-2013 06:00	24-May-2013 18:00				sage sage	Planning

2. Risk Assessment

Summary: Job Description: test
Plant Items: PPP-MIL-BLML-ML001-HE004 - HEATER, MOTOR 02

Selected Work Categories/Hazards: Working on/around Fixed plant


Selected Unwanted Events: ELECTRICAL, contact with low voltage causing injury or fatality; GRAVITATIONAL (OBJECTS) Objects falling from heights causing injury or fatality; GRAVITATIONAL (PEOPLE), Operators falling from height causing injury or fatality; MACHINE (FIXED), Uncontrolled release of energy causing injury or fatality; MAGNETIC, Strong magnetic fields causing failure of pacemakers; NOISE, Excessive noise level causing hearing damage; PEOPLE, Entrapment or crushing between moving or rotating structures causing injury or fatality; PEOPLE, Slip, Trip, Push/Pull, Sprain, Repetitive/Postural strain causing injury or fatality; THERMAL, Hot material or equipment causing burns or injury

Selected Controls: 1 Preparation Controls: Area to be physically barricaded and tagged if works are incomplete; Check all leads and power tools are fit for purpose and in good working condition; Check area for native fauna; Check area safety showers are operational and clean and run water until cool before work commences; Ensure that test tag is in place and within expiry date; Ensure work area is barricaded and tagged to protect pedestrians from potentially falling objects; Keep tooling stored in toolbox if not being used; Manual handling Training; Personal Protective Equipment (PPE); PTW system; Residual current devices in all circuits; S.L.A.M Before work commences and if conditions change; Standards & Procedures


3. Isolation Plan

Certificate Number	Isolation Point No.	Equipment / Valve / Line No.	Isolated Condition	Number of Tags	Restore To Condition	Notes
AGAA-IC-17	1	PPP-CYN-BHDAR-SU514-MT005 - MOTOR, SLUMP PUMP	LOCKED OFF	1	ON	
AGAA-IC-17	2	PPP-CYN-STTNK-TK003-V030 - 210-PI-001 PLANT AIR LINE BALL VALVE	LOCKED	1	ON	
AGAA-IC-17	3	PPP-CYN-STTNK-TK003-V040 - 210-PI-001 PLANT AIR LINE NON-RETURN VALVE	LOCKED	1	ON	
AGAA-IC-17	4	PPP-CYN-STTNK-TK003-V050 - 210-PI-001 PLANT AIR LINE BALL VALVE	LOCKED	1	ON	
AGAA-IC-17	5	LOCK BOX 2	LOCKED	1	UNLOCKED	
AGAA-IC-28	1	PPP-CRU-GCRUP-CR001-LM001 - MOTOR, CRUSHER DRIVE	RACKED OUT	1	RACKED IN	
AGAA-IC-28	2	PPP-CRU-GCRUP-CR001-LS003 - SYSTEM LUBRICATION PACK	RACKED OUT	1	RACKED IN	
AGAA-IC-28	3	LOCK BOX 6	LOCKED	1	UNLOCKED	


4. Issue Permit to Certificates




AWB: A PREDICTIVE APPROACH TO ASSET MANAGEMENT




Labor Profile




Plant Availability & Capacity






Shutdown evaluation Use of stockpiles/buffers





REGIONAL SETTING



HAVANA DEEPS PRE-FEASIBILITY STUDY





TGM GOLD MINERALISATION – CONCEPTUAL TARGETING




HARD ROCK SEISMIC



- SE plunging folds
- Control positions higher-grade shoots
- Seismic to image fold closures
- Clarify target positions
- Reduce drilling risk (shoots 80-100m wide)



EXPLORATION OVERVIEW




TROPICANA JV – MONSOON EAST





- 15km SE of Tropicana Gold Mine
- Interpreted extension of Tropicana Domain
- Undercover and largely untested by aircore drilling – wide spaced traverses only
- Extensive transported Au anomaly at adjacent Monsoon prospect
- Favourable architecture defined from structural interpretation

TROPICANA JV – MADRAS (AGA 70%)



- 24km SSE of Tropicana Gold Mine
- Significant intercepts returned from AC drilling including peak intercept of 2m @ 7.05g/t Au from 63m.
- Encouraging intercept of 6.6m @ 1.58g/t Au returned from initial diamond hole (MAD001) and 2.4m @ 5.18 g/t Au
- Favourable fold and thrust architecture defined from structural interpretation

TROPICANA JV – SEAHORSE (AGA 70%)




- 30km SSE of Tropicana Gold Mine
- Southern extension of prospective Tropicana Domain
- First pass aircore drilling returned peak result of 4m @ 0.4 g/t from 40m
- Infill aircore planned for 2014
- Little / no past exploration

AERODROME



VILLAGE FACILITIES



Dry Mess

Wet Mess

Gym/ Courts

M Site Access Road

INDIGENOUS SERVICE CONTRACTORS



CAREY MINING TRAINEESHIP PROGRAM

Carey trainees come from local and indigenous groups

- ▶ ~12 trainees at this time in variety of areas:
- ▶ Admin
- ▶ Drill and Blast
- ▶ Safety
- ▶ Operations





TROPICANA GOLD MINE



Independence Group



ANGLOGOLDASHANTI

TABLE 1: TROPICANA GOLD PROJECT (100%) DECEMBER 2013 MINERAL RESOURCES

Mineral Resource – 31 December 2013				
	Classification	Tonnes (Mt)	Au g/t	Contained Au (M Oz)
Open Pit	Measured	28.6	2.06	1.89
	Indicated	74.0	1.88	4.48
	Inferred	5.8	2.57	0.48
	Sub-Total	108.4	1.97	6.85
Underground	Measured	-	-	-
	Indicated	2.4	3.58	0.27
	Inferred	6.1	3.07	0.60
	Sub-Total	8.5	3.21	0.87
Total Tropicana	Measured	28.6	2.06	1.89
	Indicated	76.4	1.94	4.75
	Inferred	11.9	2.83	1.08
GRAND TOTAL		116.8	2.06	7.72

Notes:

For the Open Pit Mineral Resource estimate, mineralisation in the Havana, Havana South, Tropicana and Boston Shaker areas was calculated within a US\$1,550/oz pit optimisation at an AUD:USD exchange rate of 1.03 (A\$1,500/oz).

The Open Pit Mineral Resources have been estimated using the geostatistical technique of Uniform Conditioning, using cut-off grades of 0.3g/t Au for Transported and Saprolite material, 0.4g/t Au for Transitional and Fresh material.

The Havana Deeps Underground Mineral Resource estimate has been reported outside the US\$1,550/oz pit optimisation at a cut-off grade of 1.73g/t Au, which was calculated using a gold price of US\$2,000/oz (AUD:USD 1.05) (A\$1,896/oz). The Havana Deeps Underground Mineral Resource was estimated using the geostatistical technique of Ordinary Kriging using average drill hole intercepts.

Resources are inclusive of Reserves.

The Competent Persons statement is incorporated in the JORC Code Statements which follow Table Two.

JORC (2012) Table 1 Parameters are set out in the IGO website at www.independencegroup.com.au

TABLE 2: TROPICANA GOLD PROJECT (100%) – DECEMBER 2013 ORE RESERVE

Ore Reserve – 31 December 2013				
	Classification	Tonnes (Mt)	Au g/t	Contained Au (M Oz)
Open Pit	Proved	24.9	2.26	1.81
	Probable	29.9	2.02	1.95
GRAND TOTAL		54.8	2.13	3.76

Notes:

The Proved and Probable Ore Reserve (31 December 2013) is reported above economic break-even gold cut-off grades of 0.4 g/t for Transported/Upper Saprolite material, 0.5 g/t for Lower Saprolite material, 0.6g/t for Sap-Rock (Transitional) material and 0.7g/t for Fresh material at nominated gold price US\$1,100/oz, and exchange rate 0.88 AUD:USD (A\$1,249/oz Au).

The estimate is based on the actual survey position for the end of September 2013 with Resource models depleted by the monthly forecast production for the remainder of CY2013.

The Competent Persons statement is incorporated in the JORC Code Statements below.

JORC (2012) Table 1 Parameters are set out on the IGO website at www.independencegroup.com.au.

JORC Code Statements - Tropicana Gold Project Mineral Resource and Ore Reserve estimates

The information in this report that relates to Mineral Resources estimates was based on information compiled by Mr Mark Kent, a full-time employee of AngloGold Ashanti Australia Limited, who is a member of the Australasian Institute of Mining and Metallurgy. Mr Kent has sufficient experience relevant to the type and style of mineral deposits under consideration, and to the activity which has been undertaken, to qualify as a Competent Person as defined in the 2012 edition of the JORC Code. Mr Kent consented to the release of the Mineral Resource estimate, based on the information in the form and context in which it appears in this report.

The information that relates to Ore Reserves estimates was based on information compiled by Dr Salih Ramazan, a full-time employee of AngloGold Ashanti Australia Limited, who is a member of the Australasian Institute of Mining and Metallurgy. Dr Ramazan has sufficient experience relevant to the type and style of mineral deposit under consideration, and to the activity which has been undertaken, to qualify as a Competent Person as defined in the 2012 edition of the JORC Code. Dr Ramazan has consented to the release of the Ore Reserve estimate, based on the information, in the form and context in which it appears in this report.

Section 1 Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. <p>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</p>	<p>Aircore samples were collected with a scoop from spoil piles placed on the ground as one metre samples. Sampling aimed to be as representative as possible by sampling through the entire spoil pile. Samples are collected as 4m composite samples or smaller composites where required to complete the hole. Samples weigh approximately 3kg in total. Anomalous intercepts >0.05g/t Au at early stage targets are resampled at 1m intervals and resubmitted for analysis.</p> <p>Reverse Circulation (RC) samples were collected as 1m samples at the rig using a cone splitter. Two samples at a variable split of approximately 1-in-8 were collected with the resultant samples each weighing about 2-3kg. Mineralised zones and zones of geological interest were submitted to the laboratory for assay as 1m samples. Unmineralised zones were submitted to the laboratory for assay as 2m composite samples. The 2m composite samples are split through a riffle splitter and submitted for analysis. Archive 1m samples of the entire hole are retained for future sampling and check work if required.</p> <p>Diamond core (NQ2 diameter) was sampled as half core over typical down-hole widths of 1m for mineralised intervals (minimum width 0.3m maximum width 1.3m as appropriate geologically). Sampling intervals are extended across larger intervals (up to 2m) as quarter-core through unmineralised zones.</p> <p>Standards and blanks were inserted into each batch of samples submitted to the laboratory.</p>

Continued ...

Section 1 Sampling Techniques and Data *continued*

Criteria	JORC Code explanation	Commentary
Drilling techniques	Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	Aircore, RC and diamond drilling were used during the quarter. All samples from aircore drill holes were collected using standard 89mm (3.5") diameter aircore bits. RC drilling was collected using a face sampling hammer with a 127mm (5") bit. Diamond core was NQ2 diameter (75.7mm hole diameter, 50.5mm core diameter).
Drill sample recovery	Method of recording and assessing core and chip sample recoveries and results assessed.	RC and aircore sample recovery was based on visual estimates and generally good and recorded in the drill database. Wet samples were recorded in the database. Diamond core recovery is measured and logged across core runs during the core mark-up process.
	Measures taken to maximise sample recovery and ensure representative nature of the samples.	Due to the early stage of exploration, no quantitative measures were taken for sample recovery for the RC and aircore samples. Diamond core recovery was generally good. Core was reassembled for mark-up and was measured, with metre marks and down-hole depths placed on the core. Depths were checked against driller's core blocks and any discrepancies corrected after discussion with drillers. Core loss was recorded in the geological log.
	Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.	There is no obvious relationship between sample recovery and grade.

Continued ...

Section 1 Sampling Techniques and Data *continued*

Criteria	JORC Code explanation	Commentary
Logging	<ul style="list-style-type: none"> Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. 	<p>Geological logging was completed using standard logging digital data entry software and the AGA geological logs and coding system. Data on rocktype, deformation, colour, structure, alteration, veining, mineralisation and degree of weathering were recorded.</p> <p>These samples have not been used for any Mineral Resource estimation, mining studies or metallurgical studies, but the level of detail is sufficient to support Mineral Resource estimation and Mining Studies.</p>
	<ul style="list-style-type: none"> Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. 	<p>Logging is both qualitative and semi-quantitative in nature.</p> <p>All drill core is photographed.</p>
	<p>The total length and percentage of the relevant intersections logged.</p>	<p>Each hole is logged and sampled in full .</p>

Continued ...

Section 1 Sampling Techniques and Data *continued*

Criteria	JORC Code explanation	Commentary
<p>Sub-sampling techniques and sample preparation</p>	<ul style="list-style-type: none"> If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. 	<p>Aircore chips were sampled using a scoop and were generally dry, but some wet samples were collected. Samples were initially collected as 4m composites or smaller composites where required to complete the hole, with a 1m or 2m sample at the bottom of the collected to enable analysis of the freshest material. Intervals returning >0.05g/t Au at early stage targets were typically resampled from the cuttings pile with a scoop, on a 1m basis.</p> <p>RC samples were split at the rig using a cone splitter with one sample sent to Genalysis for fire assay and the other sample retained for future sampling if required.</p> <p>All diamond core has been cut into half or quarter core for sampling.</p> <p>All samples were submitted to Genalysis for lead collection fire assay for either gold only or gold, platinum and palladium analysis, and for four-acid analysis of 46 elements. Samples were oven dried at 105°C then jaw crushed to -10mm followed by a Boyd crush to a nominal -2mm. Samples were then pulverised in LM5 mills to a nominal 85% passing 75µm. Samples were analysed for gold using the Genalysis FA25/SAA technique, or for gold, platinum and palladium using the Genalysis FA25/MS technique. The FA25/SAA technique utilises a 25g lead collection fire assay with analysis by solvent extraction Atomic Absorption Spectrometry and the FA25/MS uses a 25g lead collection fire assay with analysis by Inductively Coupled Plasma Mass Spectrometry (ICP-MS). The fire assay method is considered a suitable assaying method for total Au determination. Multi-element analysis was completed using the Genalysis 4A/OM10 technique, which uses four-acid digestion with analysis of 46 elements by a combination of ICP-MS and Inductively Coupled Plasma Optical Emission Spectroscopy (ICP-OES).</p>
	<p>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</p> <ul style="list-style-type: none"> Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	<p>The sample preparation technique is appropriate and is standard industry practice for gold exploration.</p> <p>Aircore composite samples returning >0.05g/t Au are typically resampled at 1m intervals (resplit samples) and assayed as above. Where 1m resplits have been taken, these results are reported in preference to the 4m composite samples assays. No quality control procedures were adopted to prove sample representivity.</p> <p>No field duplicate samples were taken for aircore, RC or diamond samples. The drilling completed at Tropicana Q4 was for exploration only and is not used in resource estimation, where more rigorous QAQC is employed. Sample size is appropriate for the targeted mineralisation styles.</p>

Continued ...

Section 1 Sampling Techniques and Data *continued*

Criteria	JORC Code explanation	Commentary
Quality of assay data and laboratory tests	<ul style="list-style-type: none"> The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. 	The 25g fire assay technique used is a total extraction method for gold.
	<p>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</p> <p>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</p>	<p>No geophysical or XRF results are reported.</p> <p>Quality control procedures included insertion of certified standards (approximately 1 in 25), and blanks (1 in each hole). No external laboratory checks have been completed and therefore precision levels have not been established. Review of the analyses of the certified standards do not indicate any accuracy issues.</p>
Verification of sampling and assaying	<ul style="list-style-type: none"> The verification of significant intersections by either independent or alternative company personnel. 	No checks were made or required for this level of exploration.
	<ul style="list-style-type: none"> <i>The use of twinned holes.</i> 	No twin holes have been completed.
	<ul style="list-style-type: none"> <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i> 	<p>Primary data are collected in Field Marshall files on portable computers. Data are imported directly to the database using software with built in validation rules.</p> <p>Assay data are imported directly from digital assay files supplied from the laboratory and are merged in the database with sample information. Data are uploaded to a master SQL database stored in Perth, which is backed up daily.</p>
	<p><i>Discuss any adjustment to assay data.</i></p>	There has been no adjustment to assay data.

Continued ...

Section 1 Sampling Techniques and Data *continued*

Criteria	JORC Code explanation	Commentary
Location of data points	<ul style="list-style-type: none"> Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. 	Hole collars have been surveyed using a hand held GPS. Downhole surveys were completed at 30m intervals in RC and diamond holes utilising a Reflex Ez-Trac instrument. Core was orientated using the Ace Core Tool™. The dip and azimuth from the collar setup were used for aircore holes.
	Specification of the grid system used.	Drillhole location data were captured in the MGA94 grid system, Zone 51.
	Quality and adequacy of topographic control.	There is no topographical control. Holes are assigned a collar RL from a regional digital elevation model. As these holes do not form part of a resource model, it is not necessary for accurate topographic control.
Data spacing and distribution	Data spacing for reporting of Exploration Results.	Drillhole spacing varies between 50m and 400m along strike and 20-100m across interpreted strike.
	Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.	Data have not been used for a Mineral Resource estimate.
	Whether sample compositing has been applied.	No compositing, other than preliminary sample compositing, has been applied to the data.
Orientation of data in relation to geological structure	Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.	Orientation of mineralisation is unknown at this early stage.
Sample security	The measures taken to ensure sample security	<p>Samples are sealed in calico bags, which are in turn placed in large poly-weave bulka-bags for transport. Filled poly-weave bulka-bags are secured on wooden crates and transported directly via road freight to the laboratory with a corresponding submission form and consignment note.</p> <p>Genalysis checks the samples received against the submission form and notifies AGA of any missing or additional samples. Once Genalysis has completed the assaying, the pulp packets, pulp residues and coarse rejects are held in their secure warehouse. On request, the pulp packets are returned to the AGA warehouse on secure pallets where they are documented for long term storage and retrieval.</p>
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	There has been no review of sampling techniques or data.

JORC CODE, 2012 EDITION, TABLE 1 - TROPICANA EXPLORATION RESULTS 2013

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	Tropicana is a joint venture between Anglogold Ashanti (AGA) and Independence Group (IGO) (AGA:IGO, 70:30). AGA is the manager of the JV. Significant results are from several tenements within 90km of the Tropicana Mine. There are no known heritage or environmental impediments over the leases where significant results were received.
	The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	The tenure is secure at the time of reporting. No known impediments exist to operate in the area.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	The intercepts reported are from drill programs designed to follow up mineralisation discovered by AGA during regional exploration since the JV inception in 2002. The area had previously been essentially unexplored until the JV discovered gold mineralisation at Tropicana in 2005.
Geology	Deposit type, geological setting and style of mineralisation.	The host rocks are predominantly gneisses interpreted to be in the same package of rocks as the Tropicana and Havana gold deposits. Controls on mineralisation are currently unknown.

Continued ...

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Drill hole Information	<ul style="list-style-type: none"> A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: <ul style="list-style-type: none"> easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. 	<p>The easting, northing, approximate RL, dip, azimuth, hole depth, down hole length and interception depth of all intercepts <u>>2m @ 0.5g/t Au</u> are given in tables in the text of the report. Details for holes which returned <u><2m @ 0.5g/t Au</u> are not tabulated as they are not significant.</p>
	<p>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</p>	<p>The absence of the details of the holes with <u><2m @ 0.5g/t Au</u> is not considered material given the early stage of exploration at these prospects. The exploration is at an early stage and no continuity between mineralised intercepts is implied.</p>
Data aggregation methods	<ul style="list-style-type: none"> In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. <p>The assumptions used for any reporting of metal equivalent values should be clearly stated.</p>	<p>Intercepts were calculated using length-weighting above a 0.5g/t Au cut off with a minimum downhole length of 2m and maximum of 2m of internal dilution. No top-cuts have been applied.</p>

Continued ...

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Relationship between mineralisation widths and intercept lengths	<ul style="list-style-type: none"> These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. <p>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known')</p>	Intercepts reported are downhole lengths, true widths are unknown.
Diagrams	Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	A plan view of the locations of the significant intercepts is provided. Due to the early stage of exploration, sections have not been included.
Balanced reporting	<i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i>	All intercepts >2m @ 0.5g/t Au have been provided. Holes with intercepts <2m @ 0.5g/t Au have not been reported due to their large number.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	There are no other exploration data to report that are considered meaningful.
Further work	<ul style="list-style-type: none"> <i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i> <p><i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i></p>	Follow up drilling is planned in the coming quarters.

JORC CODE COMPETENT PERSON STATEMENT FOR EXPLORATION RESULTS

The information in this presentation that relates to Exploration Results is based on information reviewed by Mark Doyle, a full-time employee of AngloGold Ashanti Australia Ltd, who has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the Australian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Mark Doyle consents to the inclusion in this presentation of the matters based on his information in the form and context in which it appears.